

2043 Camden

May 28, 2010



RavelGuard®

Yarn in regular loop pile carpet is tufted with a straight stitch that may unravel and fray.

Our RavelGuard® construction is tufted with an interlocking stitch to prevent unraveling. TriBond lamination provides excellent lamination strength and tuft bind. see full warranty for details.



Stain Proof - No Exceptions™

Strudon® is inherently stain proof. Carpets made of Strudon® fiber are ideal for high stain environments including food service areas and rental units.



Scoured & Extracted™

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



Anti-shock

This carpet features permanently conductive fibers and will not generate a static shock exceeding 3.5kV at a relative humidity of 20% and a room temperature of 21°C. 3.5kV is beyond the threshold of human sensitivity and safe to use where personal computers are present.



10 Year Warranties

- Residential wear
 - RavelGuard® + no edge ravel + no delamination
 - Stain Proof – No Exceptions™
 - Anti-Shock
 - AccuPattern™
- See full text for details.

Style 2043

03 Gold Strike
14 Drift Stone

04 Burlap
18 Remain Neutral

06 Toast Brown

09 Cordwood

BARRETT

Style 2043 Camden
 Manufacturer Barrett Carpet

CONSTRUCTION

Fiber system	88% BCF Strudon® / 12% BCF nylon	
Construction	Textured graphic loop	
Standard backing system	Dual bonded woven synthetic	
Pile weight	22 oz./y ²	746 g/m ²
Pile height	0.27" / 0.19"	7 mm / 5 mm
Gauge	1/8	31.5 rows/10 cm
Stitches	9.6 s.p.i.	37.8 stitches/10 cm
Density	4000	

PROTECTION

Coloration	Solution dyed / yarn dyed
Stain resistance	Stain Proof – No Exceptions™
Soil protection	Scoured & Extracted™

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Recycling program	Eligible for recycling program	

PERFORMANCE

Static generation	3.5 kV or less (AATCC 134)	
Flammability	Canada: CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement)	
	USA:	Radiant Panel ASTM E648 – Class I DOC 1-70
Light fastness	L5	
Change on wet cleaning	Gray scale 5	

INSTALLATION

Approximate pattern repeat (w x l)	1/2" x 1"	1.3 cm x 2.5 cm
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installation	

WARRANTIES

10 year Warranties (see full text for details)	Residential wear RavelGuard® + no edge ravel + no delamination Stain Proof – No Exceptions™ Anti-Shock AccuPattern™
---	---

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice.

E&OE.

BARRETT



LEED Specifications

Style Name: Camden (broadloom)

MR 2.1 and MR 2.2

Construction Waste Management:

Recycle used broadloom in Kraus' carpet reclamation program

Contributes to up to 2 LEED points

MR 5.1

Regional Materials

Kraus products are manufactured in Waterloo, Ontario

Contributes to 1 LEED point

EQ 4.1

Low Emitting Materials: Adhesives

Kraus products are compatible with low VOC adhesives

Contributes to 1 LEED point

EQ 4.2

Low Emitting Materials: Carpet

This product meets the requirements of the Carpet & Rug Institute's Green Label Plus Indoor Air Quality Testing Program

1 LEED point