

# 455 Mount Rushmore

March 5, 2009



## RavelGuard™

Yarn in regular loop pile carpet is tufted with a straight stitch that may unravel and fray.

Our RavelGuard™ construction is tufted with an interlocking stitch to prevent unraveling. TriBond lamination provides excellent lamination strength and tuft bind. see full warranty for details.



## Scoured & Extracted™

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



## BioFresh™ Anti-microbial

This carpet incorporates BioFresh™ anti-microbial treatment to inhibit the growth of bacteria, fungi and mildew, ensuring lasting hygienic freshness. Carpets with BioFresh™ are ideal for areas where spills and soil could promote bacterial growth



## Anti-shock

This carpet features permanently conductive fibers and will not generate a static shock exceeding 3.5kV at a relative humidity of 20% and a room temperature of 21°C. 3.5kV is beyond the threshold of human sensitivity and safe to use where personal computers are present.



## Lifetime Warranties

- Commercial wear
- RavelGuard™ + no edge ravel + no delamination
- Colorfast
- Anti-Shock

See full text for details.

## Style 455

---

230 Pine Bark	239 Straw	318 Barley	414 Olive
617 Ocean Front	708 Smoke Stack	735 Flint	811 Grey Stone
838 Mulberry	841 Concorde	907 Blue Bird	942 Blueberry
944 Navy			

# BARRETT

Style Mount Rushmore  
 Manufacturer Barrett Carpet

**CONSTRUCTION**

Fiber system	100% BCF Ultrel™ nylon	
Construction	RavelGuard™ level loop	
Standard backing system	TriBonded woven synthetic	
Pile weight	28 oz./y <sup>2</sup>	950 g/m <sup>2</sup>
Pile height	0.19"	4.8 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	11.6 s.p.i.	45.7 stitches/10 cm
Density	6500 FHA	

**PROTECTION**

Coloration	86% Solution dyed / 14% yarn dyed	
Soil protection	Scoured & Extracted™ PermaSeal™ protected	
Anti-microbial protection	BioFresh™ present in backing laminate	

**SUSTAINABILITY**

CRI/CCI air quality test	Green Label Plus	GLP 4545
Recycling program	Eligible for recycling program	

**PERFORMANCE**

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.5 kV or less (AATCC 134)	
Flammability	Canada: CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) USA: Radiant Panel ASTM E648 – Class I Smoke Density ASTM E662 – Less than 450 (Flaming)	
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147	
Light fastness	L5	
Change on wet cleaning	Gray scale 5	

**INSTALLATION**

Approximate pattern repeat (w x l)	Random	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installation	

**WARRANTIES**

Lifetime Warranties (see full text for details)	Commercial wear RavelGuard™ + no edge ravel + no delamination Colorfast Anti-Shock	
--	---	--

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice.

E&OE.