

# 5014 Brasilia

Feb 17, 2009



## RavelGuard™

Yarn in regular loop pile carpet is tufted with a straight stitch that may unravel and fray.

Our RavelGuard™ construction is tufted with an interlocking stitch to prevent unraveling. TriBond lamination provides excellent lamination strength and tuft bind. see full warranty for details.



## Stain Proof - No Exceptions™

Ultrel:indelible™ solution dyed nylon offers a Stain Proof - No Exceptions™ warranty. Carpets made of Ultrel:indelible™ are ideal for high stain environments such as leaseholds and food services.



## Scoured & Extracted™

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



## Sustainability | LEED®

- 30% pre-consumer recycled content in face fiber
- Eligible for recycling program
- Low emitting product: air quality certified Green Label Plus



## Lifetime Warranties

- Commercial wear
- RavelGuard™ + no edge ravel + no delamination
- Stain Proof – No Exceptions™
- AccuPattern™
- Anti-Shock

See full text for details.

## Style 5014

01 Festas  
05 Costa  
09 Brazilwood

02 Candangos  
06 Palace of Dawn

03 Highlands  
07 Tropical Savanna

04 Monumental Axis  
08 Lake Paranoa



Blue Planet  
sustainable style

Style 5014 Brasilia

### CONSTRUCTION

Fiber system	100% BCF Ultrel:indelible™ nylon	
Construction	RavelGuard™ interlocking textured loop	
Standard backing system	Tribonded woven synthetic	
Pile weight	28 oz./y <sup>2</sup>	950 g/m <sup>2</sup>
Pile height	0.19	4.8 mm
Gauge	1/10	39.4 rows/10cm
Stitches	12.5 s.p.i.	49.2 stitches/10cm
Density	6300 FHA	13.6 kilotex/cm <sup>2</sup>

### PROTECTION

Coloration	Solution dyed / yarn dyed	
Stain resistance	Stain Proof – No Exceptions™	
Soil protection	Scoured & Extracted™	
	PermaSeal™ protected	
Anti-microbial protection	BioFresh™ present in backing laminate	

### SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4545
Recycling program	Eligible for recycling program	
Recycled content	30% pre-consumer recycled content in face fiber*	

### PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.5 kV or less (AATCC 134)	
Flammability	Canada: CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement)	
	USA: Radiant Panel ASTM E648 – Class I Smoke Density ASTM E662 – Less than 450 (Flaming)	
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147	
Light fastness	L5	
Change on wet cleaning	Gray scale 5	

### INSTALLATION

Approximate pattern repeat (w x l)	Random
Installation method	Suitable for direct glue or cushion installations
Chair protectors	Recommended for direct glue installations Mandatory for cushion installation

### WARRANTIES

Lifetime Warranties (see full text for details)	Commercial wear RavelGuard™ + no edge ravel + no delamination Stain Proof – No Exceptions™ Anti-Shock AccuPattern™
--	--

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. \*Percentages of recycled content are accurate at date of printing. The availability of these inputs could fluctuate over time. See [blueplanetcarpet.com](http://blueplanetcarpet.com) for latest specifications.

E&OE.



Blue Planet  
sustainable style