

502 Signature II

July 23, 2009



Pressure Beck Dyed for Uniform Color

Advanced dyeing technology provides more uniform color than conventional piece dye methods. Greater color consistency virtually eliminates roll-to-roll matching problems within dye lots.



BioFresh™ Anti-microbial

This carpet incorporates BioFresh™ anti-microbial treatment to inhibit the growth of bacteria, fungi and mildew, ensuring lasting hygienic freshness. Carpets with BioFresh™ are ideal for areas where spills and soil could promote bacterial growth



High Performance Cut/Uncut Texture

Precision cut/uncut carpets blend the benefits of loop and pile carpet.

- Aesthetics for areas such as boardrooms and restaurants where cut pile is traditional.
- Performance-enhanced by 50% loop pile.



Anti-shock

This carpet features permanently conductive fibers and will not generate a static shock exceeding 3.5kV at a relative humidity of 20% and a room temperature of 21°C. 3.5kV is beyond the threshold of human sensitivity and safe to use where personal computers are present.



Lifetime Warranties

- Commercial wear
- Colorfast
- Anti-Shock

See full text for details.

Style 502

917 Marine	420 Sage	315 Canyon Stone	119 Soap Stone
821 Elderberry	911 Nickel	906 Riptide	404 Laurel
118 Khaki	213 Llama	705 Ironstone	709 Platinum
601 Jade Stone			

BARRETT

Style Signature II
 Manufacturer Barrett Carpet

CONSTRUCTION

Fiber system	100% BCF nylon	
Construction	Precision cut / uncut	
Standard backing system	Dual bonded woven synthetic	
Pile weight	32 oz./y ²	1085 g/m ²
Pile height	0.25"	6.5 mm
Gauge	1/8	31.5 rows/10 cm
Stitches	12.4 s.p.i.	48.8 stitches/10 cm
Density	5300	

PROTECTION

Coloration	Pressure beck dyed
Anti-microbial protection	BioFresh™ present in backing laminate

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 1878
Recycling program	Eligible for recycling program	

PERFORMANCE

Static generation	3.5 kV or less (AATCC 134)	
Flammability	Canada: CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement)	
	USA: Radiant Panel ASTM E648 – Class I Smoke Density ASTM E662 – Less than 450 (Flaming)	
Anti-microbial performance	Contact inhibition of fungal and bacterial growth tested according to AATCC methods 30 & 147	
Light fastness	L5	
Change on wet cleaning	Gray scale 5	

INSTALLATION

Approximate pattern repeat (w x l)	1/2" x 1/2"	1.3 cm x 1.3 cm
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installation	

WARRANTIES

Lifetime Warranties (see full text for details)	Commercial wear Colorfast Anti-Shock
--	--

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice.

E&OE.

BARRETT